

STORAGE TANK HEATERS

Download the form and fill out all known information. Once complete, email to sales@heatrex.com

Date	_ Job Reference	
Company Name		
Address		
City		
Customer Contact		
Phone No		
E-Mail Address		
Date Quote Required		

APPLICATION									
Tank Dimensions:	_ Capacity:	gal.,	Tank Ma	terial:	_ Horizontal or	Vertical			
Insulation thickness:	_ in., Insulatio	n type:		R Value:					
Maintaining temp.:	°F	°F Min. /max. ambient temperatures:		°F, Indoor	or Outdoor				
Initial heat-up time required:	hou	rs	Maximu	m temp. rise during heat up:		°F			
Material to be heated:									
Fluid Properties: Density or Specific G	ravity:	at	°F	Specific heat:	at	°F			
Thermal Conduct	ivity:	at	°F	Viscosity:	at	°F			
Maximum Fluid Film Temperature:		°F							
Describe how the heater is to be used:									
Describe the process loop:									
HEATER DESIGN									
Required KW rating: or heat duty:									
Available power:	volts,		phase,	Ma	aximum watt density				
Maximum insertion length into tank:			Co	old section:					
Tank heater pipe material:(Carbon steel is standard)									
Heater Environment (NEMA Type): 1 , 4 , 4X , 7 Non-hazardous Area or Hazardous Area									
Special Items:									
CONTROLS									
Type: ON / OFF Multi S	tage	Number of Stage	s	/ Solid-state SCR ((modulated)				
NEMA Type enclosure (if remote): 12 , 4 , 4X , 7 (cast aluminum)									
Controls mounted: On heating unit (prewired) Remote control panel									
Special Control Items:									